

CLAIMS

1. Device for monitoring the water resistance of a case (2) of an electronic timepiece (1) including a time base (42) for generating a standard frequency signal and a central processing unit (44) for determining the time from the standard signal, characterized in that it includes an electronic sensor (32) capable of measuring
5 fluctuations in the concentration of a gas in the atmosphere contained in the case (2), the results of the measurement carried out by the electronic sensor (32) being processed by the central processing unit (44) which, in response to the measurement signal, emits, if necessary, an acoustic or visual warning alarm.
2. Device according to claim 1, characterized in that the electronic sensor
10 (32) includes a differential measuring bridge (48).
3. Device according to claims 1 or 2, characterized in that the gas present in the atmosphere contained in the enclosed space is an inert gas.
4. Device according to claim 3, characterized in that the concentration of
15 inert gas in the atmosphere of the enclosed space is less than its concentration in the ambient air.
5. Device according to claims 3 or 4, characterized in that the inert gas is carbon dioxide or helium.
6. Device according to any of claims 1 to 5, characterized in that the
20 enclosed space is provided with a valve (36) for forcing gas therein.
7. Device according to any of claims 1 to 6, characterized in that the sensor (32) measures the initial concentration of gas, then measures said concentration continuously or intermittently and generates an alarm signal as soon as it detects a fluctuation in the value of the concentration of the gas greater than a predetermined value.
- 25 8. Device according to any of claims 1 to 7, characterized in that the sensor (32) includes electrical heating means whose role is to keep a thermally and electrically insulated membrane at a constant temperature.
9. Method of monitoring the water resistance of a case (2) of a timepiece (1), said method being characterized in that it includes the steps consisting of:
30 - introducing a gas with an initial concentration into the atmosphere contained in the case;
- measuring the initial concentration of gas;
- continuously or intermittently measuring the concentration of gas, and

- generating an alarm when the measured concentration of gas is different from the initial concentration of said gas or when the leak rate exceeds a predetermined value.

10. Method according to claim 9, characterized in that before measuring the
5 concentration of gas, the ambient temperature is measured.

11. Method according to any of claims 8 to 10, characterized in that the case is filled with gas by opening the latter, filling it with gas, then sealing it in a water resistant manner.

12. Method according to any of claims 8 to 10, characterized in that the
10 enclosed space is filled with gas via a valve.